

	Multi-Use	Single-Use	Internal Sensor	External Sensor	4,000 Logs Memory	5,700 Logs Memory	8,000 Logs Memory	16,000 Logs Memory	User Configurable	Cradle Required	USB Connector	Display	Fixed Battery	Replaceable Battery	5V via micro USB socket	Temperature Range	Ultra-Low Temperature Range	Audible Alarm	Multiple Alarm	Temperature & Humidity	WiFi	PDF Report
--	-----------	------------	-----------------	-----------------	-------------------	-------------------	-------------------	--------------------	-------------------	-----------------	---------------	---------	---------------	---------------------	-------------------------	-------------------	-----------------------------	---------------	----------------	------------------------	------	------------

Data Logger

TRIX-8	✓		✓				✓	✓	✓							-40°C to +85°C						
TRIX-16	✓		✓					✓	✓	✓	✓					-40°C to +85°C						
TREX-8	✓			✓			✓	✓	✓	✓						-40°C to +99°C						
TRID30-7R	✓		✓				✓	✓	✓	✓		✓				-30°C to +60°C						
TRID30-7F	✓		✓				✓	✓	✓	✓		✓	✓			-30°C to +60°C						
TRIL-8	✓		✓				✓	✓	✓	✓							-80°C to +40°C					
TREL-8	✓			✓			✓	✓	✓	✓						-90°C to +40°C						
TREL30-16	✓			✓				✓	✓	✓	✓		✓			-90°C to +40°C	✓					
TRED30-16R	✓			✓				✓	✓	✓	✓		✓			-40°C to +99°C		✓				
UTRIX-16	✓		✓					✓	✓		✓		✓			-30°C to +70°C				✓		
UTRID-16	✓		✓					✓	✓		✓		✓			-30°C to +60°C		✓		✓		
HAXO-8	✓		✓				✓	✓	✓	✓						-40°C to +85°C			✓			
vaxtag	✓		✓				✓		✓	✓		✓	✓			-30°C to +60°C						
UTRED30-16	✓			✓				✓	✓		✓	✓	✓			-40°C to +99°C		✓	✓		✓	
UTRED30-WIFI	✓			✓					✓	✓		✓	✓			-40°C to +99°C		✓	✓	✓	✓	
UHADO-16	✓		✓					✓	✓		✓	✓	✓			-30°C to +70°C		✓	✓	✓	✓	
SRIC-4		✓	✓		✓				✓	✓	✓	✓				-30°C to +60°C						
SRIL-8		✓	✓				✓		✓	✓	✓					-80°C to +40°C						
USRIC-4		✓	✓		✓				✓		✓		✓			-30°C to +60°C						
USRIC-8		✓	✓					✓		✓		✓				-30°C to +60°C			✓		✓	
HASO-8		✓	✓					✓		✓		✓				-40°C to +85°C				✓		
USRID-16		✓	✓						✓	✓		✓	✓			-30°C to +60°C					✓	
UTRED-16		✓		✓					✓	✓		✓	✓			-40°C to +99°C		✓	✓		✓	
UTREL30-WIFI		✓		✓					✓	✓		✓	✓			-90°C to +40°C	✓	✓	✓	✓	✓	
UTREL30-16		✓		✓					✓	✓		✓	✓			-90°C to +40°C	✓	✓			✓	
UTREL-16		✓		✓					✓	✓		✓	✓			-90°C to +40°C		✓			✓	
USRID16W1/W2		✓	✓		✓			✓								-30°C to +60°C		✓			✓	

Temperature Indicator

TIC 20	✓	✓														-30°C to +60°C			✓		
TICT	✓	✓														-25°C to +60°C			✓		
iSOTag	✓	✓														-25°C to +60°C					

LogTag Analyzer operating software is supplied free of charge

For service and support contact your local dealer under www.logtag-recorders.com